

LUBE OIL SEPARATOR CLEANER

APPLICATIONS

LO SEPARATOR CLEANER is an especially formulated blend of surfactants, solvents and acids designed to remove carbonaceous and varnish deposits from lube-oil and fuel-oil separator discs.

DIRECTIONS FOR USE

It is recommended to immerse the discs in a diluted solution of *LO SEPARATOR CLEANER*. Depending upon the amount of deposits, use a solution containing 1 part of cleaner to 4 - 8 parts of water. Any suitable metal container (except galvanized) or dip tank can be used to contain the cleaning solution. The solution can be used at ambient temperature of 50°C - 60°C (122°F - 140°F). Do not immerse bronze or brass support column in the cleaning solution, corrosion of these materials will likely occur. Remove the stainless steel discs from the support column and place only these stainless steel parts in the cleaning solution. After cleaning has been completed, thoroughly rinse the parts with plenty of fresh water.

NATURE OF SPECIAL RISKS AND SAFETY ADVICE

In accordance with the latest EEC Council directives this product is subjected to:

R22	: Harmful if swallowed
R35	: Causes severe burns
R51/53	: Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment
S2	: Keep out of reach of children
S23	: Do not breathe gas, fumes, vapor and spray
S24	: Avoid contact with skin
S26	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S36/37/39	: Wear suitable protective clothing, gloves and eye / face protection
S45	: In case of accident or if you feel unwell, seek medical advice immediately (show the label if possible)
S60	: The material and its container must be disposed of as hazardous waste
S61	: Avoid release to the environment. Refer to special instructions / safety data sheets
S62	: If swallowed do not induce vomiting; seek medical advice immediately and show this container or label

Code:161161330



LUBE OIL SEPARATOR CLEANER

Disc cleaner

- Removes carbonaceous and varnish deposits from discs
- Reduces cleaning time
- Safe to use and does not corrode disc material

PRODUCT CHARACTERISTICS

Appearance:	clear white or amber liquid
Specific gravity:	1,06 (20°C)
pH (neat):	1,9
IMO Class:	8 / II
UN Number:	3265
ADR:	8.40b)

UNIClean