

UNICLEAN BREAK

DESCRIPTION

UNICLEAN BREAK is a heavy-duty tank and bilge cleaner. It contains wetting agents, detergents and demulsifiers. The quick separating properties leave the water-phase with less than 15 PPM of oil, which meets IMO requirements.

APPLICATIONS

UNICLEAN BREAK is used for cleaning and gas freeing of mineral oil tanks and for cleaning of tanks upgrading from black to white or grain.

It can also be used as a general cleaner in the engine room and especially for cleaning bilges.

DIRECTIONS FOR USE

TANK WASHING MACHINE

UNICLEAN BREAK is injected into the wash-waterline, at a rate of 1 lt. per ton of wash-water, through the cleaning cycle. The wash-water should be maintained between 65 - 80°C. It is important to keep the tank bottom well stripped for efficient removal of deposits.

DIRECT SPRAY

UNICLEAN BREAK is sprayed undiluted using a non-atomizing spray onto the surfaces to be cleaned. Allow a reaction time of 30 minutes to 2 hours, depending on the degree of soiling, to ensure full penetration and reaction. Wash down all surfaces with hot water of between 65 - 80°C and a pressure of at least 5.6 kg / cm².

Transfer wash-water to slop tank and allow settling and separating. Where an oil-water separator is installed, discharge from the bottom of the tank through the oil-water separator. This is the best method to meet IMO requirements.

For use as a demulsifying agent for separating oily water, add 1 lt. of product to 1000 lt. of oily water. Mix thoroughly and allow solution to stand for 4 - 6 hours for separation to take place.

NATURE OF SPECIAL RISKS AND SAFETY ADVICE

In accordance with the latest EEC Council directives this product is subjected to:

- R65 : Harmful; may cause lung-damage if swallowed
- S2 : Keep out of reach of children
- S23 : Do not breathe gas, fumes, vapor or spray
- S24 : Avoid contact with skin
- S62 : If swallowed do not induce vomiting; seek medical advice immediately and show the container or label

Code:161161313



UNICLEAN BREAK

Quick separating tank and general cleaner

- Oil and water emulsions break up quickly after cleaning
- Meets IMO requirements, less than 15 PPM of oil remains in the water-phase
- Heavy duty cleaner, suitable for removal of most mineral oils, fats and grease

PRODUCT CHARACTERISTICS

Appearance:	clear amber liquid
Density:	0,8 (20°C)
Flash point:	>63°C
IMO Class:	9 / III
UN Number:	3082
ADR:	9.11c)

UNIClean